



UNICABLE TIES

www.unicableties.com

Stainless Steel Cable Ties

Ball Lock Type Cable Ties

Ladder Type Cable Ties

Releasable Type Cable Ties

Bands, Markers & Tags



COMPANY PROFILE

The "Uni Cable Ties" are the most reliable and reputed brand delivering high quality engineering stainless steel cable ties which provide solutions to all your clamping requirements. The "Uni Cable Ties" are used in varied industries and performs host of other clamping solutions worldwide.

The "Uni Cable Ties" are uniquely designed and subjected to rigorous physical and chemical testing to ensure compliance with the international quality standards and safety of your clamping functions. The cable ties have bur free and rounded edge which makes them suitable for fast and easy applications. The cable ties are designed to withstand harsh environments and can be operated manually or by special designed hand tool.

Over 20 Years of Experience in Stainless Steel Clamping, Bundling, Fastening and Identification Solutions make us one of the largest and finest manufacturers of range of products we manufacture and supply since 1994.

We are committed to provide on-time delivery with flawless quality products. Our business transactions are transparent and hassle free, enhancing the customer experience in the buying process. Empowered with well-defined infrastructure, our experience in handling bulk order and meeting targets as per the given schedules help us in efficiency meeting customers' needs. Known for good reputation, timely delivery and high quality products make us much ahead of others. Today, our products and services are well appreciated nationally and internationally.

INDUSTRIES WE SERVE

- Automotive
- Off-Shore
- Nuclear
- Petroleum
- Chemical Industry
- Utility Industry
- Ship Building
- Fire Protection
- Electrical & Electronic
- Construction
- Communication
- General industry

BALL LOCK TYPE STAINLESS STEEL CABLE TIES

Self Locking Ball Type Stainless Steel Cable Ties provides a strong, durable bundling and fastening. Low weight, high strength of roller ball are designed for use in application where strength, vibration, weathering, corrosion extremes are a factor. It is more efficient and reliable than conventional fasteners. Quick and easy installation.

Available in Grade 316 & 304 Coated or Un-coated, in 4.6 mm and 7.9 mm widths and various lengths.

The normal operating range for the roller ball uncoated ties version is -80 °C to +538 °C approximately. For coated version normal operating range is -80 °C to +150 °C. It is available in wide choice of colors.

MINIMUM LOOP TENSILE STRENGTH:

4.6 mm width Un-coated - 130 lbs 4.6 mm width Coated - 110 lbs

7.9 mm width Un-coated - 270 lbs 7.9 mm width Coated - 200 lbs

TECHNICAL DETAILS:



Type: Roller Ball Un-coated

Width: 4.6 mm and 7.9 mm

Material: SS 304 & SS 316



Type: Roller Ball Coated

Width: 4.6 mm and 7.9 mm

Material: SS 304 & SS 316

PRODUCT CODE	WIDTH (in mm)	LENGTH (in mm)	MAXIMUM BUNDLE DIA. (in mm)
46RBU-316-100	4.6	100	20
46RBU-316-125	4.6	125	30
46RBU-316-150	4.6	150	35
46RBU-316-200	4.6	200	50
46RBU-316-250	4.6	250	70
46RBU-316-300	4.6	300	85
46RBU-316-360	4.6	360	100
46RBU-316-450	4.6	450	130
46RBU-316-520	4.6	520	155
46RBU-316-680	4.6	680	200
46RBU-316-840	4.6	840	255
46RBU-316-1000	4.6	1000	305

PRODUCT CODE	WIDTH (in mm)	LENGTH (in mm)	MAXIMUM BUNDLE DIA. (in mm)
46RBC-316-100	4.6	100	20
46RBC-316-125	4.6	125	30
46RBC-316-150	4.6	150	35
46RBC-316-200	4.6	200	50
46RBC-316-250	4.6	250	70
46RBC-316-300	4.6	300	85
46RBC-316-360	4.6	360	100
46RBC-316-450	4.6	450	130
46RBC-316-520	4.6	520	155
46RBC-316-680	4.6	680	200
46RBC-316-840	4.6	840	255
46RBC-316-1000	4.6	1000	305

PRODUCT CODE	WIDTH (in mm)	LENGTH (in mm)	MAXIMUM BUNDLE DIA. (in mm)
79RBU-316-100	7.9	100	20
79RBU-316-125	7.9	125	30
79RBU-316-150	7.9	150	35
79RBU-316-200	7.9	200	50
79RBU-316-250	7.9	250	70
79RBU-316-300	7.9	300	85
79RBU-316-360	7.9	360	100
79RBU-316-450	7.9	450	130
79RBU-316-520	7.9	520	155
79RBU-316-680	7.9	680	200
79RBU-316-840	7.9	840	255
79RBU-316-1000	7.9	1000	305

PRODUCT CODE	WIDTH (in mm)	LENGTH (in mm)	MAXIMUM BUNDLE DIA. (in mm)
79RBC-316-100	7.9	100	20
79RBC-316-125	7.9	125	30
79RBC-316-150	7.9	150	35
79RBC-316-200	7.9	200	50
79RBC-316-250	7.9	250	70
79RBC-316-300	7.9	300	85
79RBC-316-360	7.9	360	100
79RBC-316-450	7.9	450	130
79RBC-316-520	7.9	520	155
79RBC-316-680	7.9	680	200
79RBC-316-840	7.9	840	255
79RBC-316-1000	7.9	1000	305

- Ball Lock Type Cable Ties are also available in widths of 12 mm and 16 mm with various lengths for special requirements.
- Intermediate lengths are available on demand for special requirements.
- Mentioned products are also available in material SS 304, use 304 instead of 316 in Product Code e.g. 46RBU-316-100 shall be 46RBU-304-100.

LADDER TYPE STAINLESS STEEL CABLE TIES

Ladder Type Stainless Steel Cable Ties are as strong as Ball Lock type Cable Ties. The unique locking design on the strip can be applied without any crimping tool. The Ladder type ties are designed for self locking fast and easy application.

Available in Grade 316 & 304 Coated or Un-coated, in 7mm and 12 mm widths and various lengths.

Normal operating range for uncoated ties is -80 °C to +538 °C and fully coated ties is -80 °C to +150 °C. It is available in wide choice of colors. Coated ties are recommended for added resistance to corrosion, chemical and weathering effects.

MINIMUM LOOP TENSILE STRENGTH:

7 mm width - 100 lbs

12 mm width - 200 lbs

TECHNICAL DETAILS:



Type: Ladder type Un-coated

Width: 7 mm and 12 mm

Material: SS 304 & SS 316



Type: Ladder type Coated

Width: 7 mm and 12 mm

Material: SS 304 & SS 316

PRODUCT CODE	WIDTH (in mm)	LENGTH (in mm)	MAXIMUM BUNDLE DIA. (in mm)
7LTU-316-100	7	100	20
7LTU-316-150	7	150	35
7LTU-316-200	7	200	50
7LTU-316-250	7	250	70
7LTU-316-300	7	300	85
7LTU-316-360	7	360	100
7LTU-316-450	7	450	130
7LTU-316-550	7	550	165
7LTU-316-610	7	610	180
7LTU-316-680	7	680	200
7LTU-316-840	7	840	255
7LTU-316-900	7	900	275
7LTU-316-1000	7	1000	305
7LTU-316-1200	7	1200	370

PRODUCT CODE	WIDTH (in mm)	LENGTH (in mm)	MAXIMUM BUNDLE DIA. (in mm)
7LTC-316-100	7	100	20
7LTC-316-150	7	150	35
7LTC-316-200	7	200	50
7LTC-316-250	7	250	70
7LTC-316-300	7	300	85
7LTC-316-360	7	360	100
7LTC-316-450	7	450	130
7LTC-316-550	7	550	165
7LTC-316-610	7	610	180
7LTC-316-680	7	680	200
7LTC-316-840	7	840	255
7LTC-316-900	7	900	275
7LTC-316-1000	7	1000	305
7LTC-316-1200	7	1200	370

12LTU-316-100	12	100	20
12LTU-316-150	12	150	35
12LTU-316-200	12	200	50
12LTU-316-250	12	250	70
12LTU-316-300	12	300	85
12LTU-316-360	12	360	100
12LTU-316-450	12	450	130
12LTU-316-550	12	550	165
12LTU-316-610	12	610	180
12LTU-316-680	12	680	200
12LTU-316-840	12	840	255
12LTU-316-900	12	900	275
12LTU-316-1000	12	1000	305
12LTU-316-1200	12	1200	370

12LTC-316-100	12	100	20
12LTC-316-150	12	150	35
12LTC-316-200	12	200	50
12LTC-316-250	12	250	70
12LTC-316-300	12	300	85
12LTC-316-360	12	360	100
12LTC-316-450	12	450	130
12LTC-316-550	12	550	165
12LTC-316-610	12	610	180
12LTC-316-680	12	680	200
12LTC-316-840	12	840	255
12LTC-316-900	12	900	275
12LTC-316-1000	12	1000	305
12LTC-316-1200	12	1200	370

- Intermediate lengths are available on demand for special requirements.
- Mentioned products are also available in material SS 304, use 304 instead of 316 in Product Code e.g. 7LTU-316-100 shall be 7LTU-304-100.

RELEASABLE TYPE STAINLESS STEEL CABLE TIES

Releasable Type Stainless Steel Cable Ties provides easy and quick installations because of its unique design with buckle. Fasten-unfasten-refasten means greater flexibility with Releasable type Cable Ties.

Available in Grade 316 & 304 Coated or Un-coated, in 6.3 mm and 9.5 mm widths and various lengths.

The normal operating range for the uncoated ties version is -40 °C to +325 °C approximately. For coated version normal operating range is -60 °C to +170 °C. It is available in wide choice of colors. Coated ties have better weathering properties with excellent resistance to corrosion, radiation and abrasion.

TECHNICAL DETAILS:



Type: Releasable Coated and Un-coated

Width: 6.3 mm and 9.5 mm

Material: SS 304 & SS 316

MINIMUM LOOP TENSILE STRENGTH:

6.3 mm width Un-coated & Coated - 400 lbs
9.5 mm width Un-coated & Coated- 500 lbs

PRODUCT CODE	WIDTH (in mm)	LENGTH (in mm)	MAXIMUM BUNDLE DIA. (in mm)
63RLU-316-150	6.3	150	35
63RLU-316-230	6.3	230	60
63RLU-316-250	6.3	250	75
63RLU-316-300	6.3	300	85
63RLU-316-330	6.3	330	95
63RLU-316-400	6.3	400	115
63RLU-316-450	6.3	450	130
63RLU-316-520	6.3	520	155
63RLU-316-630	6.3	630	190
63RLU-316-760	6.3	760	230
63RLU-316-800	6.3	800	240
63RLU-316-850	6.3	850	260
63RLU-316-1000	6.3	1000	300

PRODUCT CODE	WIDTH (in mm)	LENGTH (in mm)	MAXIMUM BUNDLE DIA. (in mm)
63RLC-316-150	6.3	150	35
63RLC-316-230	6.3	230	60
63RLC-316-250	6.3	250	75
63RLC-316-300	6.3	300	85
63RLC-316-330	6.3	330	95
63RLC-316-400	6.3	400	115
63RLC-316-450	6.3	450	130
63RLC-316-520	6.3	520	155
63RLC-316-630	6.3	630	190
63RLC-316-760	6.3	760	230
63RLC-316-800	6.3	800	240
63RLC-316-850	6.3	850	260
63RLC-316-1000	6.3	1000	300

95RLU-316-150	9.5	150	35
95RLU-316-230	9.5	230	60
95RLU-316-250	9.5	250	75
95RLU-316-300	9.5	300	85
95RLU-316-330	9.5	330	95
95RLU-316-400	9.5	400	115
95RLU-316-450	9.5	450	130
95RLU-316-520	9.5	520	155
95RLU-316-630	9.5	630	190
95RLU-316-760	9.5	760	230
95RLU-316-800	9.5	800	240
95RLU-316-850	9.5	850	260
95RLU-316-1000	9.5	1000	300

95RLC-316-150	9.5	150	35
95RLC-316-230	9.5	230	60
95RLC-316-250	9.5	250	75
95RLC-316-300	9.5	300	85
95RLC-316-330	9.5	330	95
95RLC-316-400	9.5	400	115
95RLC-316-450	9.5	450	130
95RLC-316-520	9.5	520	155
95RLC-316-630	9.5	630	190
95RLC-316-760	9.5	760	230
95RLC-316-800	9.5	800	240
95RLC-316-850	9.5	850	260
95RLC-316-1000	9.5	1000	300

- Intermediate lengths are available on demand for special requirements.
- Mentioned products are also available in material SS 304, use 304 instead of 316 in Product Code e.g. 63RLU-316-150 shall be 63RLU-304-150.

STAINLESS STEEL BANDS, MARKERS & TAGS



STAINLESS STEEL BANDS

Stainless Steel 201 is generally used for this application. Bands with widths of 6.35 mm, 9.53 mm, 12.7 mm, 15.88 mm and 19.01 mm and thickness of 0.38 mm with various lengths are available.



STAINLESS STEEL MARKERS & TAGS

A comprehensive range of Stainless Steel Marking System is available for effortless and permanent identification of cable accessories or ducting system, even in harsh environments.

The system can be applied with Ball Lock type or Ladder type Stainless Steel Cable Ties.

We can also manufacture and supply Ball Lock type Stainless Steel Cable Ties with customized marking upon request for special requirements

DESCRIPTION	PRODUCT CODE	DIMENSIONS Width x Length (in mm)
Tag	T-3463	34 x 63
Tag	T-1951	19 x 51
Tag	T-1989	19 x 89
Tag	T-1992	19 x 92
Tag	T-892	8 x 92
Tag	T-8133	8 x 133
Tag	T-8166	8 x 166
Alphabets	A...Z	8 x 9
Numbers	0...9	8 x 9
Special Characters	+, -, ~, #, / etc.	8 x 9

- Tags are available in Stainless Steel Grade 316 & 304.
- Customized sizes are available in Markers & Tags.
- We can also manufacture Tags of special characters other than the usual ones as per specific drawing.

STAINLESS STEEL CABLE TIE TIGHTENING TOOL

Owning to our vast experience of more than 20 years of in this domain, we become able to provide a qualitative array of Cable Tie Tools which made from high grade materials with high strength and excellent performance. These tools are widely applied in various cabling application like for installing stainless steel cable ties.

Product Code: UNI-CTT-1

Key Features:

- Designed for locking all Stainless Steel Ball Lock type and Ladder type Cable Ties.
- Application as after the stainless steel tie has been tightened; push down the round steel bar at side can easily cut off rest tie.
- Lightweight design that reduces overall installer fatigue.
- Semi-auto module enables the function of tightening and cut out the rest cable tie.
- Heavy duty, two stage cable tie tool for installing stainless steel cable ties.
- Available in heavy-duty chrome-plated and PVDF coated construction for maximum corrosion resistance.
- This tool can be used with all sizes of our Ball Lock type including Double Loop style as well as Ladder type Stainless Steel Cable Ties



Product we serve:

Stainless Steel Ball Lock type Cable Ties

- 4.6 mm Ball Lock type Cable Ties
- 7.9 mm Ball Lock type Cable Ties
- 7.9 mm Double Loop Ball Lock type Cable Ties
- 12 mm Ball Lock type Cable Ties

Stainless Steel Cable Markers

- 0 to 9
- A to Z
- Symbols (+, -, /, @ etc.)

Stainless Steel Ladder type Cable Ties

- 7 mm Releasable type Cable Ties
- 12 mm Releasable type Cable Ties

Carriers for ID (Tags)

- 8 mm
- 12.5 mm
- 19 mm

Stainless Steel Ladder type Cable Ties

- 6.3 mm Releasable type Cable Ties
- 9.5 mm Releasable type Cable Ties

Stainless Steel Wing Seals (Bands)

- 6.35 mm
- 9.53 mm
- 12.7 mm
- 15.88 mm and 19.01 mm

Uni Cable Ties offers more sizes of stainless steel cable ties with more corrosion resistance and more tensile strength for superior holding power. We understand our customers and their industry challenges. We develop products that precisely fit the application, increase productivity, and mainly focus on reduce product costs.

Master Tin Works



UNI CABLE TIES

www.unicableties.com

D-10, Sardar Industrial Estate, Road No. 2, Ajwa Road, Vadodara, Gujarat, India - 390 019

Mobile: +91 91738 30303 • TeleFax: +91 265 256 1696

Email: inquiry@unicableties.com